

MADE IN FRANCE

TRASSAR[®] 251V2



Machine for road and motorway markings

- Versatile and easy to handle
- Very high productivity and long operating time
- An unrivalled reputation: over 200 machines commissioned

Areas of application:



Types of marking: line markings and specialised works

Application technique: airless

Applicable products: paints and two-component products (liquid/solid)



650 kg paint
330 kg beads

2,500 sq. metres applied
per day on average

Ergonomic design
Operating cost
Reliability/Quality

ERGONOMIC DESIGN & VERSATILITY

- **Articulated chassis for easier marking applications** on winding roads
- Width of 1.30 m **to minimise any inconvenience for road users**
- **Cockpit that can be moved** to the left or right side while maintaining access to all the controls, allowing operators to **always be aligned with the marking** and **improving user comfort**
- Wide range of adaptable options to create a truly **custom-designed machine**, including markers, manual spray gun, pre-marking arm, product filling pumps, and lights
- **Total access** to components requiring maintenance (engine, paint pump, filters, etc.)

PERFORMANCE / OPERATING COST / DURABILITY

- **Modular and scalable** machine
- Components from leading brands to guarantee **reliability, robust and durable** equipment
- Airless paint pump for producing **extra-wide markings (90 cm at airports)**
- Separable paint and glass bead tanks for **using different colours and products**
- Suction circuit for drawing paint into a separate container **to avoid cleaning** tanks when using a **coloured product**
- **Easy remarking of old lines** with the detection cells
- **Extended engine maintenance intervals** (oil change every 500 hours or once a year)

SUSTAINABLE DEVELOPMENT / ENVIRONMENT

- Over **96% recyclable**
- Machine designed for use with **water-based** paints, which are highly recommended as an alternative to harmful solvent-based paints, to help **decarbonise road marking operations**

Extra product + benefits:

Internal combustion engine with a **particulate filter** meeting applicable **environmental standards**

SPECIFICATIONS



Paint tanks	2 x 210 litres (2 x 325 kg)
Bead tanks	2 x 110 litres (2 x 165 kg)
Airless paint pump flow rate	32 litres/min
Internal combustion engine power	43.7 kW / 58.6 hp
Unladen / laden weight	2,520 kg / 3,500 kg